



LC-HD Uniboot with Pull Tab

Features:

- ◆ **Easy to release trigger connector**
GH LC-HD's lever design utilizes a flexible "pull-tab" allowing for the connector to be disengaged easily from densely loaded panels without the need for special tools.
- ◆ **60% increase in density**
Because GH LC-HD connector can be removed using a simple pull tab, it eliminates the need for finger access to the LC latch mechanism, therefore LC adaptors can now be mounted much closer than spacing required in the past.



LC-HD Uniboot with Pull Tab

Order Information:

Connector type	Ferrule ID	Housing Color	Boot Type	Boot Color
LC-HD Simplex	SM: Premium 125	SM: Blue	LC-HD Mini 900um	White
LC-HD Duplex	SM: Low Loss 125	MM: Beige	LC-HD Mini 2.0mm	
	MM: Premium MM	SM APC: Green	LC-HD Mini 3.0mm	
		MM: OM3 Aqua		

LC Duplex Switchable Uniboot Connector

Feature:

- ◆ Low insertion loss and back reflection loss
- ◆ Ferrule end surface pre-domed
- ◆ High precision alignment
- ◆ ROHS compliant
- ◆ Nickel plated brass body
- ◆ Free-floating ceramic ferrule
- ◆ Bayonet style housing for easy termination



Order Information:

Descriptions	SM(PC)	SM(APC)	MM(PC)
Insertion loss	<0.25dB	<0.25dB	<0.3dB
Return loss	≥55dB	≥65dB	≥35dB
Durability	<0.1dB typical change,500 mating		
Operating Temperature	- 40°C to + 75°C		

www.hy-fiber.com

www.hy-fiber.com